

EKI-2741 Series

10/100/1000TX to Fiber Optic Gigabit Industrial Media Converters



EKI-2741F

EKI-2741LX

EKI-2741SX



Features

- Provides 1 x 1000 Mbps Ethernet port with RJ45 connector
- Provides 1 x 1000 Mbps fiber port with SC or SFP (mini-GBIC) type connector for 1000Base-SX/LX device
- Provides DIP switch for full/half duplex setting
- Supports MDI/MDI-X auto crossover
- Supports auto-negotiation
- Supports 3,000 V_{DC} surge (EFT) protection
- Supports 4,000 V_{DC} Ethernet ESD protection
- Supports redundant +12-48 V_{DC} power input
- Provides flexible mounting: DIN-rail & Wallmounting
- Provides Link Fault Pass-through (LFP)
- Supports wide operating temperatures from -40~75° C (EKI-2741LX)

Introduction

EKI-2741 is designed to convert Gigabit Ethernet networks to Gigabit fiber networks by transparently converting Ethernet signals to optic signals. Therefore, EKI-2741 is an ideal solution for “fiber to building” applications at central offices or local sites. EKI-2741 supports MDI/MDIX auto detection, so you don’t need to use crossover wires. Furthermore, the EKI-2741 accepts a wide voltage range from +12 ~ 48 V_{DC}. Besides, it also provides 3,000 V_{DC} surge (EFT) protection against over-voltage, so it is suitable for harsh operating environments.

EKI-2741 is an enhanced gigabit Ethernet to fiber optic converter. Aside from its standard features, the versatile EKI-2741 also has the LFP (Link Fault Pass-through) feature. When one side of the link fails, the other side continues transmitting packets, and waiting for a response that never arrives from the disconnected side. EKI-2741 will force the link to shut down as soon as noticed that the other link has failed, giving the application software a chance to react to the situation.

Specifications

Communications

- Standard** IEEE802.3, 802.3u, 802.3ab, 802.3x, IEEE 802.3z
- LAN** 10/100/1000Base-TX, 1000Base-SX or 1000Base-LX
- Transmission Distance** Ethernet: Up to 100 m
Fiber:
Multi-mode: Up to 550 m
Single-mode: Up to 10 km (2741LX) or 110 km (2741F)
SFP: Up to 110 km (2741F)
- Transmission Speed** Up to 1000 Mbps

Interface

- Connectors** 1 x RJ-45
1 x SC type fiber connector (EKI-2741SX/LX) or
1 x SFP type fiber connector (EKI-2741F)
6-pin removable screw terminal (power & relay)
- LED Indicators** P1, P2, P-Fail
Fiber: LNK/ACT
Ethernet: 1000M, LNK/ACT
- DIP Switch** Port Alarm, LFP

Power

- Power Consumption** 5.28 W (EKI-2741F)
5.18 W (EKI-2741SX)
5.30 W (EKI-2741LX)
- Power Input** 2 x Unregulated 12 ~ 48 V_{DC}

Mechanism

- Dimensions (W x H x D)** 37 x 140 x 95 mm
- Enclosure** IP30, Metal shell with solid mounting kits
- Mounting** DIN-rail, Wall

Protection

- ESD (Ethernet)** 4,000 V_{DC}
- Surge (EFT for power)** 3,000 V_{DC}
- Power Reverse** Present
- Overload** 0.9 A/12 Vdc (Resettable Fuse)

Environment

- Operating Temperature** -10 ~ 60° C (14 ~ 140° F)
Wide Temp Model -40 ~ 75° C (-40 ~ 167° F)
- Storage Temperature** -40 ~ 85° C (-40 ~ 185° F)
- Operating Humidity** 5 ~ 95% (non-condensing)
- Storage Humidity** 0 ~ 95% (non-condensing)
- MTBF** 515,600 hrs (EKI-2741F)
525,300 hrs (EKI-2741SX/LX)

Certifications

- Safety** UL 60950-1, CAN/CSA-C22.2 No.60950
- EMC** U.S.A.: FCC Part 15 CISPR 22
EU: EN55011, EN61000-6-4, EN55022 Class A,
EN61000-3-s2/3, EN55024,
IEC61000-4-2/3/4/5/6/8, EN61000-6-2
- Shock** IEC60068-2-27
- Freefall** IEC60068-2-32
- Vibration** IEC60068-2-6

Ordering Information

- EKI-2741F** Industrial Gigabit Ethernet to SFP Type Fiber Optic Converter
- EKI-2741SX** Industrial Gigabit Ethernet to 1000Base-SX SC Type Fiber Optic Converter
- EKI-2741LX** Industrial Gigabit Ethernet to 1000Base-LX SC Type Fiber Optic Converter
- EKI-2741LXI** Industrial Gigabit Ethernet to 1000Base-LX SC Type Fiber Optic Converter, Wide Temp.