


R10L210-MRM2

10.4" Marine Display



KEY FEATURES

- 10.4" 800 x 600 resolution
- 24 V DC power supply with terminal block (Default, isolation resistance)
- Certified DNVGL-CG-0339, IEC60945 4th, IACS E10
- Dimming knob to control backlight brightness from nearly 0% to 100%
- Ease-of-use front panel OSD control
- Enhanced shock and vibration resistance
- IP66 aluminum housing with powder coating design (IP54 rear)
- Picture-in-picture (PIP) function and multi-video inputs
- Resistive touch screen (Optional protection glass w/o touch function)




SPECIFICATIONS

Display			
Resolution	800x600	Size	10.4 inches
Contrast Ratio	400:1	Panel Brightness	600 nits
Display Color	262K Colors	View Angles	70,70,70,60
Type	Resistive Touch Screen Transflective Film for sunlight readable(Optional) AR Glass(Optional)		
Environment			
Operating Humidity	5% to 95%	Operating Temperature	-15~55°C
Shock	15G, 11ms duration	Vibration	0.7g@DNVGL CG-0339 (Class A)
IP rating	IP66 (Front Side)		
Certification			
Certification	DNVGL-CG-0339, IEC60945 4th, IACS E10, CE, FCC		
IO Ports			
Serial Port	1 x RS-232 for Touch Screen(Optional) 1 x RS-232 for Remote Control(Optional)	Video	1 x D-SUB 15P Connector(Female) 1 x RCA Phono Plug 1 x S-Video (SVHS) Plug 1 x DVI-D Input 24 Pin Connector
Mechanical			
Dimension	339 x 256 x 72 mm	Mounting	Panel (Flush) mount with Ip66*, VESA, Bracket mounting
Enclosure	Metal	Cooling System	Fanless Design
Power			
Power Rating	24V DC-in with Isolation (Approval by Certificate) 9~36V DC Input Accpetable		
Accessory			
Accessory	1 x User Manual.	Optional Accessory	1 x Transflective LCD User Guide.(Optional)

1 x CD for Touchscreen Driver Tools.
 1 x DVI Cable.
 (DVI-D 24 Pin Male to 24 Pin Male: 1.5m.)
 1 x Std VGA Cable.
 (D-SUB 15 Pin Male to 15 Pin Male: 1.8m)
 2 x RS232 Std Serial Cable.
 (D-SUB 9 Pin Male to 9 Pin Female: 2m)
 1 x S-Video Cable.
 (MD 4 Pin Male to 4 Pin Male: 1.8m)
 1 x Composite Cable.
 (Std RCA 3.2mm Connector: 1.8m)
 4 x M6 x 30 Black Screw Bolt with M6 Nut.
 M4 x 15 Black Screw Bolt.

1 x Standard Power Cord.(Optional)
 Euro / U.S. Std Type, 1.8m(Optional)

DIMENSIONS UNIT:MM



NOTE

1. This is a simplified drawing and some components are not marked in detail.
2. Please contact our sales representative if you need further product information.
3. All specifications are subject to change without prior notice.
4. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.