

Features

- NVIDIA® Jetson™ TX2 NX
- 8GB LPDDR4
- Multi-storage option: 16GB eMMC / MicroSD slot / 2.5 drive bay
- GbE LAN x 5
- USB 3.2 Gen 1 x 4
- Wide voltage DC-in 10-24Vdc

Specifications

System		
Al Accelerator	NVIDIA® Jetson™ TX2 NX	
СРИ	NVIDIA® Denver 2 (Dual-Core) Processor & ARM® Cortex® -A57 MPCore (Quad-Core) Processor	
System Memory	4GB 128-bit LPDDR4 @ 1600 MHz	
Storage Device	eMMC 5.1 16GB Micro SD card slot x 1 2.5" SATA drive bay x 1 (for high version)	
Display Interface	HDMI Type A x 1 for HDMI 2.0	
Ethernet	RJ-45 x 5 for GbE LAN	
1/0	USB Type A x 4 for USB 3.2 Gen 1 DB-9 x 2 for RS-232 HDMI Type A x 1 for HDMI 2.0 MicroSD slot x 1 Micro USB x 1 for 0.S Flash Recovery button x 1 Power button with power LED x 1 Antenna opening x 2	
Expansion	SATA III (6.0 Gbps) Port x 1 for 2.5" SATA drive (for high version)	
Indicator	Power LED x 1	
OS Support	nVIDIA Ubantu 18.04	
Power Supply		
Power Requirement	DC-in 10V~24V with 2-pin terminal block ATX mode	
Mechanical		
Mounting	Wall mount kit	
Dimensions (W x D x H)	6.92" x 3.94" x 1.54" (175.8mm x 100.0mm x 39.0mm) 6.92" x 3.94" x 2.41" (175.8mm x 100.0mm x 61.3mm, High version)	
Gross Weight	TBD	
Net Weight	TBD	
Environmental		
Operating Temperature	$5^\circ\text{F}\sim149^\circ\text{F}$ (- $15^\circ\text{C}\sim65^\circ\text{C}$, according to IEC60068-2 with 0.5 m/s AirFlow) $5^\circ\text{F}\sim158^\circ\text{F}$ (- $15^\circ\text{C}\sim70^\circ\text{C}$, according to IEC60068-2 with 0.5 m/s AirFlow, High version)	
Storage Temperature	-40°F ~ 176°F (-40°C ~ 80°C)	
Storage Humidity	5 ~ 95% @ 40°C, non-condensing	
Anti-Vibration	3.5Grm / 5~500Hz / operation (eMMC, MicroSD, or SSD)	
Anti-Shock	50G peak acceleration (11 msec. duration, eMMC, microSD, or SSD)	
Certification	CE / FCC class A	

Dimension	Unit: mm	A
		® Edg
		Al@Edge Solutions
		lution
		18